

ITEM SERVICED	PROCEDURE	620 MI.	6200 MI.	12,400 MI.	24,800 MI.	31,000 MI.	37,200 MI.	43,400 MI.	NOTES
		1000 KM	10000 KM	20,000 KM	30,000 KM	40,000 KM	50,000 KM	60,000 KM	
Engine oil	Replace	X	X	X	X	X	X	X	1
Engine oil filter cartridge	Replace	X		X		X		X	
Air cleaner	Replace filter element as required			X		X		X	
Crankcase breather	Clean or replace			X		X		X	
Tires	Check condition, check pressure and tread	X	X	X	X	X	X	X	
Clutch fluid	Check level	X	X	X	X	X	X	X	3
Rear belt and sprocket	Inspect	X	X	X	X	X	X	X	2
Throttle, brake, clutch controls, sidestand	Inspect, service as required	X	X	X	X	X	X	X	2
Brake fluid	Check levels and condition	X	X	X	X	X	X	X	3
Brake pads and discs	Inspect for wear	X	X	X	X	X	X	X	
Spark plugs	Replace			X		X		X	2
Electrical switches and equipment	Check operation	X	X	X	X	X	X	X	
Front fork oil	Replace				X			X	2
Exhaust system	Inspect for leaks, cracks, and loose or missing fasteners or heat shields	X	X	X	X	X	X	X	5
Battery	Check battery and clean connections								5
Cooling system	Inspect level, check clamps for tightness	X	X	X	X	X	X	X	2
Coolant		Replace every 31,000 miles 40,000 kilometers							2, 6
Radiators and oil cooler fins	Clean	X	X	X	X	X	X	X	
Brake system and oil lines	Inspect for leaks	X	X	X	X	X	X	X	2
Critical fasteners	Check tightness			X		X		X	2
Valve clearance	Inspect			X		X		X	4, 2
Road test	Verify component and system functions	X	X	X	X	X	X	X	

- NOTES:**
1. Perform annually or at specified interval, whichever comes first.
  2. Should be performed by an authorized Buell dealer, unless you have the proper tools, service data and are mechanically qualified.
  3. Change D.O.T. 4 fluid and flush brake and clutch systems every two (2) years.
  4. Could vary with frequency of operation and riding style.
  5. Perform annually.
  6. Perform every two years or at specified interval, whichever comes first.